

Easy To Operate

Built-in Recirculation

Low Maintenance Cost

Low Startup Cost

Even Spray Pattern



Area 18"x24"

Spray Area upto 18"x24"
Suitable for most DTG
printers in the market



Touch Position

Touch to set the
position to be sprayed
with precise value



4x Nozzles

4x of Nozzles to choose
for different spray widths




Recirculation

Pretreatment can be
easily recirculated OR
flushed/loaded in
seconds



Density Control

Precise Density Control
sprays minimum
pretreatment amount
and produces durable
prints



Valve Control

Valves provide easy
change of pretreatment
OR change of cleaning
solution



Spray Area	max 18 x 24 inch
Nozzles	4x
Width	4.5 9 13.5 18 inch
Length	4 to 24 inch
Liquid Tanks	3x (Pretreatment, Cleaning Solution, Waste)
Spray Control	Pulse Width Modulation
Density Levels	Apprx 14g 16g 18g 20g 22g 25g per 14"x17" Area
Nozzle Type	Stainless Steel
Spray Speed	apprx 1 second
Motor	Stepper Motor
Control	5" Colour Touch Screen
Filter	Pump Inlet Filters Nozzle Filters
Dimension	W 80cm x L 91cm x H 62cm
Weight	65kg
Voltage	220 V or 110 V (optional) 200 W



Hongjet Technology Sdn Bhd
9, Lorong Perusahaan Ringan 1,
Kawasan Perusahaan Ringan,
68100 Selangor, Malaysia
www.hongjet.com.my

For more info, contact us at:
Tel: +603-6188 8880
Email: sales@hongjet.com.my